
NAME

GPStr - Glycerolipids (GP) structure generation methods

SYNOPSIS

```
use GPStr;  
  
use GPStr qw(:all);
```

DESCRIPTION

GPStr module provides these methods:

- ExpandGPCmpdAbbrevs - Expand GP abbreviation
- GenerateCmpdOntologyData - Generate ontology data
- GenerateCmpdOntologySDDataLines - Generate ontology data lines for SD file
- GenerateGPChainStrData - Generate chain structure data
- GenerateSDFile - Generate SD file
- GetGPTemplatesData - Get templates data
- GetGPSupportedHeadGroupMap - Get supported headgroups data
- GetGPTemplateID - Get templates ID
- IsGPChainsAbbrevSupported - Is it a supported GP abbreviation
- ParseGPAbbrev - Parse GP abbreviation
- SetupGPCmpdAbbrevTemplateDataMap - Setup template structure data map
- ValidateGPAbbrev - Validate GL abbreviation

METHODS**ExpandGPCmpdAbbrevs**

```
$ExpandedAbbrevArrayRef = ExpandGPCmpdAbbrevs($CmpdAbbrev);
```

Return a reference to an array containing complete GP abbreviations. Wild card characters in GP abbreviation name are expanded to generate fully qualified GP abbreviations.

GenerateCmpdOntologyData

```
$DataHashRef = GenerateCmpdOntologyData($CmpdDataRef);
```

Return a reference to a hash containing ontology data with hash keys and values corresponding to property names and values.

GenerateCmpdOntologySDDataLines

```
$DataLinesArrayRef = GenerateCmpdOntologySDDataLines($CmpdDataRef);
```

Return a reference to an array containing ontology data lines suitable for generate SD file data block.

GenerateGPChainStrData

```
($AtomLinesArrayRef, $BondLinesArrayRef) =  
    GenerateGPChainStrData($ChainType, $CmpdDataRef);
```

Return array references containing atom and bond data lines for SD file. Appropriate atom and bond data lines are generated using chain type and abbreviation template data.

GenerateSDFile

```
GenerateSDFile($SDFileName, $CmdAbbrevsRef);
```

Generate a SD file for compound abbreviations. Structure data for specified abbreviation is generated sequentially and written to SD file.

GetGPTemplatesData

```
$TemplatesDataRef = GetGPTemplatesData();
```

Return a reference to a hash containing GP templates data

GetGPSupportedHeadGroupMap

```
$SupportedHeadGroupDataRef = GetGPSupportedHeadGroupMap();
```

Return a reference to a hash containing supported head groups data.

GetGPTemplateID

```
$HeadGroupID = GetGPTemplateID($HeadGroupAbbrev, $ChainsAbbrev);
```

Return a supported template ID for compound abbreviation.

IsGPChainsAbbrevSupported

```
$Status = IsGPChainsAbbrevSupported($Abbrev, $PrintWarning);
```

Return 1 or 0 based on whether GP abbreviated is supported. For unsupported GP abbreviations, a warning is printed unless PrintWarning flag is set.

ParseGPAbbrev

```
($HeadGroup, $ChainsAbbrev, $AbbrevModifier) =  
  ParseGPAbbrev($Abbrev);
```

Parse GP abbreviation and return these values: HeadGroup, ChainsAbbrev, AbbrevModifier.

SetupGPCmpdAbbrevTemplateDataMap

```
$AbbrevTemplateDataMapRef =  
  SetupGPCmpdAbbrevTemplateDataMap($Abbrev);
```

Return a reference to a hash containing template data for compound abbreviation. The template data is used to generate SD file for compound abbreviation.

ValidateGPAbbrev

```
$Status = ValidateGPAbbrev($Abbrev);
```

Return 1 or 0 based on whether a GP abbreviation is valid.

AUTHOR

Manish Sud

CONTRIBUTOR

Eoin Fahy

SEE ALSO

ChainStr.pm

COPYRIGHT

Copyright (C) 2006. The Regents of the University of California. All Rights Reserved.